

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

BLACK BORDERS

- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

TAMPON

THOMAS WARD OSBORN III

DIANE MARGARET WELLING

JOSEPH ANTHONY GATTO

5

FIELD OF THE INVENTION

This invention relates to tampons comprising a plurality of first surfaces and a plurality of second surfaces.

BACKGROUND OF THE INVENTION

10 A wide variety of absorbent catamenial tampons have long been known in the art. It is known that the surface characteristics of a tampon may be altered physically and/or chemically to confer both aesthetic and functional benefits. The surface of tampons can be altered to have non-uniform surface topography. Some examples of tampons with non-uniform topography include a tampon that has absorbent filaments such as in U.S. Patent No. 3,695,270 issued to Dostal on October 3, 1972, and a tampon with a braided or rope shaped body such as in U.S. Patent No. 15 4,361,151 issued to Fitzgerald on November 20, 1982 and U.S. 4,328,804 issued to Shimatani on May 11, 1982. Other tampons comprise longitudinal ribs on the outer surface such as in U.S. 5,403,300 issued to Howarth on April 4, 1995, U.S. Patent No. 5,592,725 issued to Brinker on January 14, 1997, and U. S. Patent No. 5,718,675 issued to Leijd on February 17, 1998 and a tampon having spiral grooves on the outer surface such as in WO 02/078586 published on 20 October 10, 2002. While it has been found that these tampons perform their intended function tolerably well, even the best of them do not always imbibe menstrual fluid at a rate sufficient to provide good coverage against leakage. The present invention has been designed to achieve these goals while also providing an aesthetically pleasing exterior appearance for the wearer.

SUMMARY OF THE INVENTION

25 A tampon for feminine hygiene having an insertion end, a withdrawal end, a length, a longitudinal axis, and an outer surface. The tampon is comprised of compressed fibrous material. The outer surface of the tampon comprises a first region and second region. The first region has a first coefficient of friction and the second region has a second coefficient of friction different than

the first coefficient of friction. The first coefficient of friction can be greater than the second coefficient of friction.

In one non-limiting example, the first region can be located within the insertion end. In another non-limiting example, the second region can be located within the withdrawal end.

The second region of the tampon can comprise a surface coating. Moreover, the outer surface can comprise a plurality of recessed portions which can be parallel to the longitudinal axis. The recessed portions can be spirally shaped. The outer surface can have a plurality of raised portions.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the tampon.

FIG. 2 is a cross-section view along 2-2 of the tampon of FIG. 1.

FIG. 3 is a perspective view of an alternative embodiment of the tampon.

FIG. 4 is a perspective view of an alternative embodiment of the tampon.

FIG. 5 is a perspective view of an alternative embodiment of the tampon.

FIG. 6 is a perspective view of an alternative embodiment of the tampon.

FIG. 7 is a perspective view of an alternative embodiment of the tampon.

DETAILED DESCRIPTION OF THE INVENTION

As used herein "applicator" refers to a device or implement that facilitates the insertion of a tampon, medicament, treatment device, visualization aid, or other into an external orifice of a mammal, such as the vagina, rectum, ear canal, nasal canal, or throat. Non-limiting specific examples of such include any known hygienically designed applicator that is capable of receiving a tampon may be used for insertion of a tampon, including the so-called telescoping, tube and plunger, and the compact applicators, an applicator for providing medicament to an area for prophylaxis or treatment of disease, a spectroscopy containing a microcamera in the tip connected via fiber optics, a speculum of any design, a tongue depressor, a tube for examining the ear canal, a narrow hollow pipe for guiding surgical instruments, and the like.

As used herein, the term "bicomponent fibers" refers to fibers that have been formed from at least two different polymers extruded from separate extruders but spun together to form one fiber. Bicomponent fibers are also sometimes referred to as conjugate fibers or multicomponent fibers. The polymers are arranged in substantially constantly positioned distinct zones across the cross-section of the bicomponent fibers and extend continuously along the length of the bicomponent fibers. The configuration of such a bicomponent fiber may be, for example, a sheath/core arrangement wherein one polymer is surrounded by another or may be a side-by-side arrangement, a pie arrangement or an "islands-in-the-sea" arrangement.

As used herein, "compression" refers to the process of pressing, squeezing, compacting or otherwise manipulating the size, shape, and/or volume of a material to obtain a tampon having a vaginally insertable shape. The term "compressed" refers to the state of a material or materials subsequent to compression. Conversely, the term "uncompressed" refers to the state of a material or materials prior to compression. The term "compressible" is the ability of a material to undergo compression.

As used herein, the term "density" is used with its common technical meaning with units of g/cm^3 or g/cc . The density may refer specifically to that of a specific region or feature of the tampon as noted. The density will be measured, unless otherwise noted, by taking the weight divided by the geometric volume described by the shape. Unless noted, density refers to that of the overall structure and not the individual components, and will include in the measurement void volume of small pores and voids within the overall structure.

The term "digital tampon" refers to a tampon which is intended to be inserted into the vaginal canal with the user's finger and without the aid of an applicator. Thus, digital tampons are typically visible to the consumer prior to use rather than being housed in an applicator.

The term "folded" as used herein, is the configuration of the tampon pledget that may be incidental to lateral compaction of the absorbent material or may purposely occur prior to a compression step. Such a configuration is readily recognizable, for example, when the absorbent material abruptly changes direction such that one part of the absorbent material bends and lies over another part of the absorbent material.

As used herein, "generally cylindrical" refers to the usual shape of tampons as is well known in the art, but which also includes oblate or partially flattened cylinders, curved cylinders, and shapes which have varying cross-sectional areas (such as a Coke™ bottle shape). The

longitudinal axis refers to the longest linear dimension of the tampon. The cross-section refers to a slice taken at right angles to the longitudinal axis.

5 The term "joined" or "attached," as used herein, encompasses configurations in which a first element is directly secured to a second element by affixing the first element directly to the second element; configurations in which the first element is indirectly secured to the second element by affixing the first element to intermediate member(s) which in turn are affixed to the second element; and configurations in which the first element is integral with the second element; i.e., the first element is essentially part of the second element.

10 As used herein, the term "longitudinal axis" of a tampon refers to the axis that runs through the center of the tampon as shown in FIG. 1. A portion of the tampon may be asymmetric about the longitudinal axis, such as when the withdrawal end region is flared and distorted from the original shape of the rest of the tampon (such as a "fin shape"). Further, the longitudinal axis may be linear or non-linear.

15 The "outer surface" of a tampon refers to the visible surface of the (compressed and/or shaped) tampon prior to use and/or expansion. At least part of the outer surface may be smooth or alternatively may have topographic features, such as ribs, spiraling ribs, a mesh pattern, or other topographical features.. Typically, tampons are constructed from an absorbent material, which has been compressed and/or shaped in any or all of the width direction, the radial direction, and the axial direction, in order to provide a tampon which is of a size and stability to allow insertion
20 within the vagina or other body cavity.

The term "cross-section," as used herein, is any 5 mm section orthogonal to the longitudinal axis.

25 As used herein, the terms "pledget" or "tampon pledget" are intended to be interchangeable and refer to a construction of absorbent material prior to the compression and/or shaping of such construction into a tampon as described above. Pledgets may be rolled, folded or otherwise manipulated prior to compression. Tampon pledgets are sometimes referred to as tampon blanks, or softwinds, and the term "pledget" is intended to include such terms as well. In general in this specification, the term "tampon" is used to refer to a finished tampon after the compression and/or shaping process. It will be recognized by those of skill in the art that in some
30 contexts these terms are interchangeable. The different stages of tampon manufacture are described herein with an eye toward providing the greatest possible clarity. Therefore, the terms

used are to assist the reader in best understanding the features of the invention and not to introduce limitations in the terms not consistent with the context in which they are used in this specification.

As used herein, the term "radial axis" of a tampon refers to the axis that runs at right angles to the longitudinal axis of the tampon as shown in FIG. 1.

The term "rolled," as used herein, is the configuration of the tampon pledget after winding the absorbent material upon itself.

As used herein, a tampon has a "self-sustaining shape" when a tampon pledget has been compressed and/or shaped such that it assumes a general shape and size, which is vaginally insertable, absent external forces. It will be understood by one of skill in the art that this self-sustaining shape need not, and preferably does not persist during actual use of the tampon. That is, once the tampon is inserted and begins to acquire fluid, the tampon may begin to expand and may lose its self-sustaining form due to the acquisition of the fluid.

As used herein, the term "tampon," refers to any type of absorbent structure that is inserted into the vaginal canal or other body cavities for the absorption of fluid therefrom, to aid in wound healing, or for the delivery of active materials, such as medicaments, or moisture. The tampon may be compressed into a generally cylindrical configuration in the radial direction, axially along the longitudinal axis or in both the radial and axial directions. While the tampon may be compressed into a substantially cylindrical configuration, other shapes are possible. These may include shapes having a cross section that may be described as rectangular, triangular, trapezoidal, semi-circular, hourglass, serpentine, or other suitable shapes. Tampons have an insertion end, withdrawal end, a length, a width, a longitudinal axis, a radial axis and an outer surface. The tampon's length can be measured from the insertion end to the withdrawal end along the longitudinal axis. A typical compressed tampon for human use is 30-60 mm in length. A tampon may be straight or non-linear in shape, such as curved along the longitudinal axis. A typical compressed tampon is 8-20 mm wide. The width of a tampon, unless otherwise stated in the specification, corresponds to the length across the largest cylindrical cross-section, along the length of the tampon.

The term "vaginal cavity," "within the vagina," and "vaginal interior," as used herein, are intended to be synonymous and refer to the internal genitalia of the mammalian female in the pudendal region of the body. The term "vaginal cavity" as used herein is intended to refer to the

space located between the introitus of the vagina (sometimes referred to as the sphincter of the vagina or hymeneal ring,) and the cervix. The terms "vaginal cavity," "within the vagina" and "vaginal interior," do not include the interlabial space, the floor of vestibule or the externally visible genitalia.

5 FIG. 1 shows a tampon 20 of the present invention. The tampon 20 can be any shape in the art and any type of tampon known in the art. FIG. 1 shows a shaped tampon, such as that disclosed in currently pending and commonly assigned, U.S. Patent Application Serial No. 10/150050, filed March 18, 2002, entitled "Substantially Serpentine Shaped Tampon," to Randall, et al. and currently pending and commonly assigned, U.S. Patent Application Serial No.
10 10/150055, filed March 18, 2002, entitled "Shaped Tampon," to Kollowitz, et al. Not to be bound by theory, it is believed that the topographic feature of the present invention increases greater surface area of the tampon allowing for improved fluid imbibition, thus, providing improved coverage against leakage.

15 FIG. 1 illustrates a tampon for feminine hygiene, having an outer surface 22, an insertion end 24, a withdrawal end 26, a length l, a radial axis R and a longitudinal axis L. The tampon 20 of the present invention may have or not have a uniform density over a cross section of the tampon 20. Alternatively, the tampon 20 may have portions that are more or less dense than other portions, such as a core, which may be highly compressed. A tampon 20 having varying densities is described in greater detail in co-pending patent application filed November 4, 2003, entitled
20 "Substantially Serpentine Shaped Tampon with Varying Density Regions", to Almond, Docket Number 9419 and co-pending patent application filed November 4, 2003, entitled "Substantially Serpentine Shaped Tampon with Varying Density Regions", to Almond, Docket Number 9418.

25 The tampon 20 has a first region 40 and a second region 42. The first region 40 may be located in any place on the tampon 20. In one non-limiting example, the first region 40 can be located in the insertion end 24. Likewise, the second region 42 may be placed anywhere on the tampon 20. In one non-limiting example, the second region 42 can be located in the withdrawal end 26.

30 The tampon 20 of the present invention is comprised of compressed fibrous material. The first region's 40 coefficient of friction is different than the second region's 42 coefficient of friction. The first region's 40 coefficient of friction may be greater than the second region's 42 coefficient of friction. Alternatively, the first region's 40 coefficient of friction may be less than the second region's 42 coefficient of friction.

Many ways to change the coefficient of friction are well-known in the art. The coefficient of friction may be changed by surface coating. The surface coating may be placed anywhere on the tampon 20. In one non-limiting example, the surface coating may be placed on the second region 42. In addition, the coefficient of friction may be changed by a lubricious coating such as that disclosed in currently pending and commonly assigned, U.S. Patent Application Serial No. 60/473082, filed May 23, 2003, entitled "Lubricious Article," to Osborn, et al. Moreover, the coefficient of friction may be changed by using microbeads within or on the surface of the tampon 20. The microbeads may have a diameter of less than about 1000 microns, less than about 250 microns, and preferably less than about 100 microns. Microbeads can be composed of many materials. Such materials include but are not limited to Polymethyl Methacrylate, polyethylene, ethylene/acrylate copolymer, nylon-12, silicon resin, crosslinked Polymethyl Methacrylate, polyurethane, and surface treated highly porous silica. Compositions for microbeads may also be used on the outer surface 22 of the tampon 20 such as Microsilk (available from Presperse Inc., Piscataway, NJ 08854) and Shin-etsu Chemical Co., Ltd., (Tokyo, Japan). Furthermore, the coefficient of friction may be changed by a lubricious coating such as that disclosed in currently pending and commonly assigned, U.S. Patent Application Serial No. 60/473082, filed May 23, 2003, entitled "Lubricious Article," to Osborn, et al. Moreover, coefficient of friction may also be changed to gels, waxes, lotions, creams, hydrogel as noted in U.S. Patent No. 5, 073, 365 issued to Katz et al., U.S. Patent No. 4,312,348 issued to Friese et al., U.S. Patent No. 6,379,702 issued to Lorenz et al., U.S. Patent No. 4,847,324 issued to Creasy, U.S. Patent No. 4,100,309 issued to Micklus et al., U.S. Patent No. 5,420, 197 issued to Lorenz et al., U.S. Patent No. 5, 533,990 issued to Yeo et al., U.S. Patent No. 4,300, 561 issued to Kaczmarzyk et al., U.S. Patent No. 3,796,219 issued to Hanke, and U.S. Patent No. 5,201,326 issued to Kubicki et al.

Referring to FIG. 2, moreover, a plurality of recessed portions 23 may change the coefficient of friction. Alternatively, at least a portion of the first region 40 may comprise recessed portions 23. The tampon 20 may have recessed portions 23 selected from the group consisting of longitudinal recessed portions 23, horizontal recessed portions 23, and mixtures thereof. The outer surface 22 of the tampon 20 may comprise a plurality of longitudinal recessed portions 23, as shown in FIG. 2. Each of the longitudinal recessed portions 23 on the outer surface 22 of the tampon 20 may have a length less than 5 mm. The longitudinal recessed portions 23 may be positioned along the entire length of the tampon. The longitudinal recessed portions 23 may be parallel to the longitudinal axis L. The longitudinal recessed portions 23 may be arranged randomly on the outer surface 22 of the tampon 20. Alternatively, the longitudinal

recessed portions 23 may be arranged in a pattern on the outer surface 22 of the tampon 20. The pattern of longitudinal recessed portions 23 on the outer surface 22 of the tampon 20 may be diagonal lines, as shown in FIG. 3, straight lines as shown in FIG. 3, checkerboard, and mixtures thereof. The longitudinal recessed portions 23 on the outer surface 22 of the tampon 20 may be evenly spaced. The insertion end 24 of the tampon 20 may comprise more longitudinal recessed portions 23 than the withdrawal end 26. The recessed portions 23 may also be horizontal recessed portions 23. The horizontal recessed portions 23 may extend the entire radial axis R of the tampon 20.

The plurality of recessed portions 23 may be any shape known including amorphous, geometric, or a combination thereof. The recessed portions 23 may be symmetric or asymmetric. The recessed portions 23 may be any two or three-dimensional geometric shape known including but not limited to ovals, circles, rectangles, trapezoids, triangles, cones, squares, spirally shaped, rectangles, quadrilaterals, pentagons, hexagons, septagons, octagons, nonagons, decagons, parallelograms, rhombuses, trapeziums, alphabet letters, trademarks, logos, and mixtures thereof. The recessed portions 23 on the outer surface 22 of the tampon 20 may be arranged randomly or in a pattern. The pattern of recessed portions 23 on the outer surface 22 of the tampon 20 may be diagonal lines, straight lines, checkerboard, and mixtures thereof. The recessed portions 23 on the outer surface 22 of the tampon 20 may be evenly spaced.

The recessed portions 23 may have various cross-sectional shapes. The recessed portions 23 may be relatively "peaked" with a fairly sharp axis where the two slopes join or they may be relatively rounded at that point to completely rounded, e.g., hemispherical bulges above the primary surface of the tampon. The longitudinal recessed portions 23 in cross-section may be symmetrical such that each slope is basically a mirror image of the other, or they may be asymmetrical wherein, for example, one slope is relatively steep and the other relatively shallow. The longitudinal recessed portions 23 may have a single peak or vertex where two slopes join, or a multiplicity of such peaks, or none at all, as is the case wherein the slope is so gradual that the rounded hemispherical shape is evident. The vertex may be spirally shaped. Further, it may be desirable that the basic width of the recessed portion 23 vary along the length of this feature such that it may have width "a" in one region and width "b" in another and "c" in yet another, either with smooth progression in width or an abrupt change in width as is required for aesthetic reasons.

Referring to FIG. 4a, a plurality of raised portions 28 may also change the coefficient of friction. The plurality of raised portions 28 may be any shape known including amorphous, geometric, or a combination thereof. The raised portions 28 may be symmetric or asymmetric.

The raised portions 28 may be any two or three-dimensional geometric shape known including but not limited to ovals, circles, rectangles, trapezoids, triangles, cones, squares, spirally shaped, rectangles, quadrilaterals, pentagons, hexagons, septagons, octagons, nonagons, decagons, parallelograms, rhombuses, trapeziums, alphabet letters, trademarks, logos, and mixtures thereof. The raised portions 28 on the outer surface 22 of the tampon 20 may be arranged randomly or in a pattern. The pattern of raised portions 28 on the outer surface 22 of the tampon 20 may be diagonal lines, straight lines, checkerboard, and mixtures thereof. The raised portions on the outer surface 22 of the tampon 20 may be evenly spaced. Referring to FIG. 4a, the raised portions 28 may have amplitude A as measured adjacent to the outer surface 22 of from about 0.5 mm to about 6 mm. The raised portions 28 may have a maximum width W as measured adjacent to the outer surface 22 of from about 0.5 mm to about 6 mm. It is believed that the raised portions 28 on the outer surface 22 of the tampon enlarge the absorptive surface of the tampon 20 increasing the absorptive capacity of the tampon 20. Moreover, it is believed that the raised portions 28 provide quicker expansion and provides longer distances for the menses to traverse before leakage occurs around the tampon 20.

Alternatively, at least a portion of the first region 40 may comprise recessed portions 23. The tampon 20 may have recessed portions 23 selected from the group consisting of longitudinal recessed portions 23, horizontal recessed portions 23, and mixtures thereof. The outer surface 22 of the tampon 20 may comprise a plurality of longitudinal recessed portions 23, as shown in FIG. 4b, FIG. 5 and FIG. 6. Each of the longitudinal recessed portions 23 on the outer surface 22 of the tampon 20 may have a length less than 5 mm. The longitudinal recessed portions 23 may extend the entire length of the tampon. The longitudinal recessed portions 23 may be parallel to the longitudinal axis L. The longitudinal recessed portions 23 may be arranged randomly on the outer surface 22 of the tampon 20.

The region within a defined portion may be dictated by the surface features, such as aberrations and grooves. Thus, while the defined portion will have a defined dimension, the surface are within that portion will always be different from the defined dimension if surface features such as aberrations and grooves are present within the defined portion.

Referring to FIG. 5, alternatively, at least a portion of the first region 40 may comprise grooves 50. The tampon 20 may have grooves 50 selected from the group consisting of longitudinal grooves 50, horizontal grooves 50, and mixtures thereof. The outer surface 22 of the tampon 20 may comprise a plurality of longitudinal grooves 50, as shown in FIG. 5. Each of the longitudinal grooves 50 on the outer surface 22 of the tampon 20 may have a length less than 5 mm. The longitudinal grooves 50 may vary in width or may have uniform widths. The longitudinal grooves 50 may extend the entire length of the tampon. The longitudinal grooves 50

may be parallel to the longitudinal axis L. The longitudinal grooves 50 may be arranged randomly on the outer surface 22 of the tampon 20. Alternatively, the longitudinal grooves 50 may be arranged in a pattern on the outer surface 22 of the tampon 20. The pattern of longitudinal grooves 50 on the outer surface 22 of the tampon 20 may be straight lines as shown in FIG. 5, checkerboard, diagonal lines, and mixtures thereof. The longitudinal grooves 50 on the outer surface 22 of the tampon 20 may be evenly spaced. The insertion end 24 of the tampon 20 may comprise more longitudinal grooves 50 than the withdrawal end 26.

The grooves 50 may also be horizontal grooves 50 as in FIG. 6 and FIG. 7. The horizontal grooves 50 may extend the entire radial axis R of the tampon 20. The horizontal grooves 50 may vary in width or may have uniform widths. The horizontal grooves 50 may be arranged randomly on the outer surface 22 of the tampon 20. Alternatively, the horizontal grooves 50 may be arranged in a pattern on the outer surface 22 of the tampon 20. The horizontal grooves 50 on the outer surface 22 of the tampon 20 may be evenly spaced. The insertion end 24 of the tampon 20 may comprise more horizontal grooves 50 than the withdrawal end 26.

The grooves 50 may have various cross-sectional shapes. The grooves 50 may be relatively "peaked" with a fairly sharp axis where the two slopes join or they may be relatively rounded at that point to completely rounded, e.g., hemispherical bulges above the primary surface of the tampon. The longitudinal grooves 50 in cross-section may be symmetrical such that each slope is basically a mirror image of the other, or they may be asymmetrical wherein, for example, one slope is relatively steep and the other relatively shallow. The longitudinal grooves 50 may have a single peak or vertex where two slopes join, or a multiplicity of such peaks, or none at all, as is the case wherein the slope is so gradual that the rounded hemispherical shape is evident. Further, it may be desirable that the basic width of the longitudinal groove 50 vary along the length of this feature such that it may have width "a" in one region and width "b" in another and "c" in yet another, either with smooth progression in width or an abrupt change in width as is required for aesthetic reasons. It will be obvious to one ordinary skill that the longitudinal grooves 50 may adopt myriad possible cross-section shapes, much as is the case with geographic ridges on the surface of a planet.

Tampon pledget may be constructed from a wide variety of liquid-absorbing materials commonly used in absorbent articles. Such materials include but are not limited to rayon (such as GALAXY Rayon SARILLE L rayon both available from Acordis Fibers Ltd., of Hollywall, England), cotton, bicomponent fibers, polyethylene, polypropylene, other suitable natural or

synthetic fibers known in the art, and mixtures thereof. Other materials that may be incorporated into the tampon pledget including comminuted wood pulp which is generally referred to as airfelt, folded tissues, woven materials, nonwoven webs, peat moss, absorbent foams (such as those disclosed in U.S. Patent No. 3,994,298 issued to DesMarais on November 30, 1976 and U.S. Patent No. 5,795,921 issued to Dyer, et al.,) capillary channel fibers (such as those disclosed in U.S. 5,356,405 issued to Thompson, et. al on October 18, 1994), high capacity fibers (such as those disclosed in U.S. Patent No. 4,044,766 issued Kaczmarzk, et al. on August 30, 1977), superabsorbent polymers or absorbent gelling materials (such as those disclosed in 5,830,543 issued to Miyake, et al. on November 3, 1998).

10 The tampon pledget is generally square or rectangular, but other shapes such as trapezoidal, triangular, hemispherical, chevron and hourglass shaped are also acceptable. A more detailed description of liquid-absorbing materials and pledget shapes and dimensions can be found in currently pending and commonly assigned, United States Patent Serial No. 10/039,979, filed October 24, 2001, entitled "Improved Protection and Comfort Tampon," to Agyapong, et al.

15 A typical size for tampon pledget prior to compression may be from about 40 mm to about 100 mm in length and from about 40 mm to about 80 mm in width. In general, the pledget material may be from about 40 mm to about 60 mm in length and from about 50 mm to about 70 mm in width. The typical range for the overall basis weight is from about 150 g/m² to about 800 g/m². The tampon pledget material may be a laminar structure comprised of integral or discrete layers.

20 Alternatively, the tampon pledget may not have a layered structure at all. The tampon pledget may have or uniform density or in the alternative may have portions that are more or less dense than other portions, such as a core, which is highly compressed.

The tampon 20 of the present invention may optionally comprise an overwrap comprising material such as rayon, cotton, bicomponent fibers, polyethylene, polypropylene, other suitable

25 natural or synthetic fibers known in the art, and mixtures thereof. The tampon 20 may have a nonwoven overwrap comprised of bicomponent fibers that have a polypropylene core surrounded by polyethylene manufactured by Vliesstoffwerke Christian Heinrich Sandler GmbH & Co.KG (Schwarzenbach/Saale, Germany) under the tradename SAS B31812000. The tampon 20 may comprise a nonwoven overwrap of a hydroentangled blend of 50% rayon, 50% polyester available

30 as BBA 140027 produced by BBA Corporation of South Carolina, U.S. The overwrap may be 100% polyester. The overwrap may be treated to be hydrophilic, hydrophobic, wicking or non-wicking. The tampon pledget may also contain a variety of other adjuvants such as odor control

agents, antibacterial agents, colorants, indicators for various kinds of illnesses such as yeast infections, indicator features for signaling when the tampon should be changed, and the like.

The tampon of the present invention may comprise a secondary absorbent member. The secondary absorbent member may be comprised of material such as rayon, cotton, bicomponent
5 fibers, polyethylene, polypropylene, polyester, other suitable natural or synthetic fibers known in the art, and mixtures thereof. The secondary absorbent member may be single ply or multiple plies. The secondary absorbent member may be absorbent and/or hydrophilic. The secondary
10 absorbent member 30 may be attached to the second end 38 of the tampon pledget, such that after folding and compression, the secondary absorbent member 30 is attached to the withdrawal end
26 end of the tampon 20. The secondary absorbent member 30 may be arranged in a wide variety of shapes and configurations and may be generally cylindrical, spherical, semi-spherical, disc-
like, planar, rectangular, "sheet-like," "skirt-like" in shape. The secondary absorbent member 30
may range in length from about 10 mm to about 40 mm from the withdrawal end 26 of the
tampon 20. The secondary absorbent member 30 may be from about 20 mm to about 25 mm in
15 length, from about 6 mm to about 40 mm in width, and from about 0.5 mm to about 5 mm in thickness.

Withdrawal members 32 useful in the present invention may be made of any suitable material known in the prior art and include cotton and rayon. In addition, the withdrawal member
32 can take on other forms such as a ribbon, loop, tab, or the like. The withdrawal member 32
20 may be integral with the tampon pledget. The withdrawal member 32 or regions of the withdrawal member 32 may be treated to be non-absorbent, absorbent or hydrophilic. The withdrawal member 32 may be attached in any suitable manner known in the art including sewing, adhesive attachment, bonding, thermal bonding, or a combination thereof including the method disclosed in currently pending, commonly assigned, U.S. Patent Application Serial No.
25 10/610,075, filed June 30, 2003, entitled "Method and Apparatus for Cord Attachment" to Sargent, et al.

The tampon 20 of the present invention may be inserted digitally. It may be desirable to provide a finger indent at the withdrawal end 26 of the tampon 20 to aid in insertion, if the
tampons 20 are to be digital tampons. An example of a finger indent can be found in U.S. Patent
30 6,283,952, filed May 5, 1997, entitled "Shaped Tampon," issued to Child, et al.

Alternatively, the insertion may be aided through the use of any applicator adapted from the prior art. Prior art applicators having a typical "tube and plunger" type arrangement may be

plastic, paper, or other suitable material. Additionally, a "compact" type applicator is also suitable. Where the tampon 20 of the present invention is shaped and provides aesthetic appeal to consumers, it is may be desirable to combine the shaped tampon with an applicator type which enables the user to observe at least a portion or the whole shape of the shaped tampon 20. Two techniques which allow the user to better notice the shape of the tampon 20 are to either make visual observation possible through the use of a translucent or even transparent applicator materials, or to provide a tampon applicator insertion end that better follows and hence better displays the profiled shape of the enclosed shaped tampon than the typical commercial tampon applicators comprising straight-walled cylindrical inserter tubes often made from molded plastic or laminated cardboard tubes. These techniques may be found in currently pending and commonly assigned, U.S. Patent Application Serial No. 10/150055, filed March 18, 2002, entitled "Shaped Tampon," to Kollowitz, et al.

The tampons 20 of the present invention can optionally be packaged in wrappers which are loose, conforming, tightly conforming and mixtures thereof to the outer surface 22 of the tampon 20 in order to visually show the consumer the tampon packaged therein. Tightly conforming wrappers are particularly useful when the shaped tampons are intended to be used digitally and therefore are not housed in an applicator prior to use. The wrappers should substantially enclose each individual tampon 20 and are removed prior to insertion and use. "Tightly conforming," means that there is substantially no visually noticeable void space between the wrapper and the tampon 20. In some embodiments of the present invention, some regions of the wrapper material may provide additional functional benefits, such as cord deployment means. Since tampons 20 are typically made by compressing fibrous absorbent material into a self-sustaining shape, the tightly conforming wrapper can optionally be used to act with a certain compressing force on the outer surface 22 of the tampon 20, which will aid in maintaining the self-sustaining shape by counteracting the expansion of the compressed material. Such wrappers are discussed in detail currently pending and commonly assigned, U.S. Patent Application Serial No. 10/150055, filed March 18, 2002, entitled "Shaped Tampon," to Kollowitz.

While several methods of making the tampon 20 of the present invention should be apparent to one of skill in the art in light of the disclosure herein, following is a description of one method of making a tampon 20 of the present invention.

The tampon 20 of the present invention is made by providing the material that comprises the tampon pledget, withdrawal member 32, attaching or joining these components, folding the

components and compressing. In making the tampon 20 of the present invention, the tampon pledget is provided. Next, the withdrawal member 32 is provided. The withdrawal member 32 may be attached in any suitable manner known in the art including sewing, adhesive attachment, bonding, thermal bonding, or a combination thereof, including the method disclosed in currently
5 pending, commonly assigned, U.S. Patent Application Serial No. 10/610,075, filed June 30, 2003, entitled "Method and Apparatus for Cord Attachment" to Sargent, et al.

Next, the combination of the tampon pledget, secondary absorbent member 30 and withdrawal member 32 are folded or rolled. To form a tampon ready for use, the tampon pledget is typically compressed and heat conditioned in any suitable conventional manner including the
10 method disclosed in currently pending, commonly assigned, U.S. Patent Application Serial No., filed May 12, 2003, entitled "A Process for Producing Stabilized Tampons," to Prosis, et al. Pressures and temperatures suitable for this purpose are well known in the art. Typically, the tampon pledget may be compressed in both the radial and axial direction using any means well known in the art. While a variety of techniques are known and acceptable for these purposes, a
15 modified tampon compressor machine available from Hauni Machines, Richmond, VA, is suitable. Optionally, a finger indent can be made using a compression rod. An example of a finger indent can be found in U.S. Patent 6,283,952, filed May 5, 1997, entitled "Shaped Tampon" issued to Child, et al. The secondary absorbent member 30 may be attached to the tampon 20 before or after compression, and then no modification of the method of making a
20 conventional compressed absorbent tampon is necessary.

All documents cited in the Detailed Description of the Invention are, in relevant part, incorporated herein by reference; the citation of any document is not to be construed as an admission that it is prior art with respect to the present invention.

While particular embodiments of the present invention have been illustrated and
25 described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.


What is claimed is:

1. A tampon for feminine hygiene, comprising an insertion end, a withdrawal end, a length, a longitudinal axis, and an outer surface;
said tampon being comprised of compressed fibrous material;
wherein said outer surface of said tampon comprises a first region and second region, said first region having a first coefficient of friction and said second region having a second coefficient of friction different than said first coefficient of friction.
2. The tampon according to Claim 1 wherein said first coefficient of friction is greater than said second coefficient of friction.
3. The tampon according to Claim 1 wherein said first region is located within said insertion end.
4. The tampon according to Claim 1 wherein said second region is located within said withdrawal end.
5. The tampon according to Claim 1 wherein said second region further comprises a surface coating.
6. The tampon according to Claim 5 wherein said surface coating is a lubricious coating wherein said lubricious coating is bound to said outer surface of said tampon.
7. The tampon according to Claim 1 wherein said second region further comprises microbeads wherein said microbeads is bound to said outer surface of said tampon.
8. The tampon according to Claim 1 wherein said second region further comprises wherein said microbeads is bound to said outer surface of said tampon.
9. The tampon according to Claim 1 wherein said second region further comprises a composition selected from the group consisting of waxes, gels, lotions, and creams.
10. The tampon according to Claim 1 wherein said outer surface further comprises a plurality of recessed portions.

11. The tampon according to Claim 8 wherein said recessed portions are parallel to said longitudinal axis.
12. The tampon according to Claim 8 wherein said recessed portions are spirally shaped.
13. The tampon according to Claim 1 wherein said outer surface further comprises a plurality of raised portions.

ABSTRACT

A tampon for feminine hygiene, having an insertion end, a withdrawal end, a length, a longitudinal axis, and an outer surface. The tampon has compressed fibrous material. The outer surface of the tampon has a first region and second region. The first region has a first coefficient of friction and the second region has a second coefficient of friction different than the first coefficient of friction.

$\frac{1}{5}$ 

2
5




Fig. 2







Fig. 3

$\frac{3}{5}$ 

4/5



5/5

